

arkaos® VS1

AN INDUSTRIAL STRENGTH
DESIGN WITH A
BLISTERINGLY FAST
GRAPHICS ENGINE



PERFECT FOR INSTALLS.
TINY, RELIABLE, AND SIMPLE TO USE.
1 X 4K OUTPUT POWERED BY ARKAOS PRO.

arkaos®

E: contact@arkaos.com

www.arkaos.com

Battlesesteenweg 455, E19 Business Park, Building A2, B-2800 Mechelen Belgium

ARKAOS®

VS1 MEDIA SERVER



Technical Informations **arkaos®** VS1

I/O SPECIFICATIONS	VS1
INTERFACE OUTPUT	1X HDMI - 4K
OUTPUT	1X HDMI - 4K
ETHERNET	1X 2.5GB/S CAT5E
USB	1X USB 3 (FRONT) 2X USB 3 AND 2X USB-C (BACK)
BACKPLATE	NO
SYNC	NO
INPUT	NO
STORAGE	VS1
SYSTEM DRIVE	SSD 500GB
DATA DRIVE	NO
SYSTEM RESTORE DRIVE	NO
SOFTWARE	VS1
OPERATING SYSTEM	WINDOWS 11 PRO
ARKAOS APPLICATION	PRO
LED MAPPER	YES
KLING-NET MAPPER	YES
VIDEO MAPPER	YES
FACTORY RESTORE SYSTEM	NO
PLAYBACK LAYERS	48
SOFT-EDGE / GEOMETRICAL CORRECTION	YES
CONTROL	VS1
CONTROL DISPLAY (FRONT PANEL)	NO
LED STRIP (FRONT PANEL)	NO
DMX / MIDI / KEYBOARD	YES
ARTNET / MA-NET	YES
HARDWARE	VS1
CPU	INTEL I7
#THREADS (CORES)	8 (4)
RAM	16GB (2 X 8GB)
TYPE	DDR4 3200MHZ SODIMM
GRAPHICAL CARDS	INTEL INTEGRATED GRAPHICS
POWER INPUT CONNECTOR	TRUECON
VOLTAGE	107-240 V 50-60 HZ
PROFESSIONAL CONNECTORS	NO